



Ground Reinforcement System

ECORASTER[®] Bloxx

Specifications

ECORASTER® Bloxx – The New Block Paver

For fast installation of permeable ground reinforcement with concrete paver design



Technical Data

Dimensions:	330 mm x 330 mm x 50 mm 12.99 X 12.99 x 1.97 inches
Weight:	approx. 85 kg 187.39 lbs (incl. blocks)
Locking System:	36 T-elements /m ² 6 T-elements/ sqft
Dimensional Stability (Temperature):	-50° to +90 ° C -58° F to +194°F
Block Dimensions:	140 x 140 x 45mm (each) 5.51 x 5.51 x 1.77 inches
Weight per Block:	approx. 2.12 kg 4.67 lbs
Available Colours:	red, white, dark grey and light grey

The advantages

- ✓ Permeable Ground Rainforcment
- ✓ Variable and Flexible Applications
- ✓ Heavy load
- ✓ High rate of installation
- ✓ Proven Safety Locking System
- ✓ Fits seamlessly in all ECORASTER® Systems
- ✓ Resistant to UV and aggressive solvents
- ✓ Easy maintainance, long-lasting
- ✓ Made in Germany
- ✓ Environmentally Neutral
- ✓ 100% Recycled Content

Delivery units

Transport version:	standard
Concrete blocks per pallet:	432 pcs.
ECORASTER® Bloxx modules per pallet:	108 pcs. (9 layers, each 1.33m ²)
Area per pallet:	11.97m ² 128.79 sqft
Weight per pallet (approx):	1 ton 2.204.62 lbs
Other picking and packing options available on request.	

Applications

- » Parking lots
- » Universal Accessibility
- » Driveways
- » Pedestrian and bicycle paths

Accessories

PURUS offer accessories for ECORASTER® ground reinforcement systems, including hinge and curve adaptors as well as parking markers.

Note: Please follow our installation instructions and guideline available on our website.

Take advantage of our years of experience and technical know-how, which we implement daily in desing and manufacturing of our quality products.



PURUS PLASTICS GmbH
Am Blätterrangen 4
95659 Arzberg

Tel.: +49 9233 7755-0
Fax: +49 9233 7755-50
info@purus-plastics.de

www.purus-plastics.de

ECORASTER® is a Trademark of PURUS PLASTICS GmbH